



WI-2004
1 SATA 4ch Analog HD DVR



Features:

- Support D1 series front-end real-time encoding ,AHD-L series front-end non-real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

WI-2004

Interface:



Parameter:

	Model	WI-2004
System	Main processor	Huawei Hi 3515C
Video	video codec	H.264(High Profile);
	Encode	4*D1 real-time /4*AHD-L*12fps
	Decode	2*D1 real-time /4*AHD-L*12fps
Audio	Multi-mode input	Pure Analog: 4*AHD-L; 4*D1; Mixed: 2*D1(analog) +1*720P (network) +1* 960H(network); Pure Network: 1*1080P; 4*1080P, 8*D1
	Audio compression	G.711A
Recording and Playback	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Storage and backup	Playback Channels	4 (pure local input mode)
	Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
Interface	Backup mode	Network backup、USB HDD, USB writer、SATA writer
	Video input	4 BNC
	Video output	1ch VGA,1ch HDMI,1ch TV
	Audio input	4ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	1 SATA (Each maximum support 4T)
Wireless	No	
Other	Power	12V/2A
	dimension	255mm(length)* 236mm(width)* 44mm(height)