



WI-2008T
2 SATA 8ch Analog HD DVR



Features:

- Support D1 series front-end real-time encoding ,AHD-L series front-end non-real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Model:

WI-2008T

Interface:



Parameter:

	Model	WI-2008T
System	Main processor	Huawei Hi 3520D
Video	video codec	H.264(High Profile);
	Encode	8*D1 real-time /8* AHD-L@12fps
	Decode	1*D1 real-time /2* AHD-L@12fps
	Multi-mode input	Pure Analog: 8* AHD-L ; 8*D1; 8*HD1; Mixed: 2*D1 (Analog) +1*1080P (Network) +1*720P (Network) ; Pure Network: 8*1080P; 4*720P; 8* 720p ; 1*1080P,4*1080P;
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	2 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
	Backup mode	Network backup、 USB HDD, USB writer、 SATA writer
Interface	Video input	8 BNC
	Video output	1ch VGA,1ch HDMI,1ch TV
	Audio input	4ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2 SATA (Each maximum support 4T)
Other	Wireless	No
	Power	12V/2A
	dimension	325mm(length)* 240mm(width)* 52mm(height)