



**WI-2016T**  
2 SATA 16ch Analog HD DVR



**Features:**

- Support D1 series front-end real-time encoding ,AHD-L series front-end non-real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

**Model:**

**WI-2016T**

**Interface:**



**Parameter:**

	Model	WI-2016T
System	Main processor	Huawei Hi 3521
Video	video codec	H.264(High Profile);
	Encode	16*D1 real-time /16* AHD-L@12fps
	Decode	1*D1 real-time /4* AHD-L@12fps
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	4 (pure local input mode)
Storage and backup	Space occupation	960H: 12~20G/ day*channel 720P: 20G~30G/ day*channel audio: 691.2M/ day*channel
	Backup mode	Network backup、 USB HDD, USB writer、 SATA writer
Interface	Video input	16 BNC
	Video output	1ch VGA,1ch HDMI,1ch TV
	Audio input	2ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2 SATA ( Each maximum support 4T )
Other	Wireless	3G、 WIFI(expand via USB)
	Power	12V/2A
Other	dimension	255mm(length)* 236mm(width)* 44mm(height)