



**WI-DP7302A**

## ■ Overview

Very thanks for you use our company products

These products use the latest high definition CMOS image sensor, and combined with our company technology. have a good stability, high sensitivity, crystal-clear picture quality, beautiful shape and easy to install, can be good application your CCTV system.

## ■ Product Characteristic

- Plastic dome camera
- 1/3" CMOS 1000TVL
- Lens: 3.6/ 6/ 8 mm optional
- IR led light: Ø5(850nm) x 24 LEDS
- IR distance: 20M

## ■ Parameters Of Product

Items	Parameters
Image Sensor	1/3" CMOS PC1099
Effective pixels	762(H)* 560(V)
Sync System	Internal
Minimum illumination	0.03 Lux (IR ON)
Resolution	1000TVL
Auto White Balance	AUTO
Gain Control	AUTO
S/N Ratio	≥48dB (AGC OFF)
Auto Electronic Shutter	NTSC: 1/60~1/100,000 sec.
	PAL: 1/50~1/100,000 sec.
B.L.C.	AUTO
Video Output	Composite 1.0V p-p at 75 ohm
Gamma Correction	0.45
Operation Temperature	-10°C TO 50°C
Humidity	within 85%RH
Power Supply	DC12V±1V / 280mA±10mA
Dimensions (L x W x H)	100mm* 100mm* 90mm
Lens	3.6mm
Weight	300g

\* Specifications are subject to change without notice.